

## SPECIFICATIONS

<b>BED WIDTH – 83”</b>	<b>BED LENGTH – 192”</b>	<b>AXLE – (2) 7,000# 8 LUG MULTI-LEAF SPRINGS WITH E-Z LUBE HUBS</b>	<b>TIRE – 235/80R/16</b>	<b>WHEEL- 16” SILVER MODULAR</b>
<b>COUPLER- 2-5/16” Gooseneck adjustable coupler</b>	<b>COUPLER HEIGHT 38”-42” adjustable</b>	<b>FLOOR HEIGHT – 29”</b>	<b>WALL HEIGHT- 24”</b>	<b>APPROX. CUBIC YARD CAPACITY- 7.9</b>
<b>G.V.W.R. 14,000#</b>	<b>TRAILER WEIGHT – 4,000#</b>	<b>NET PAYLOAD – 10,000#</b>	<b>FRAME – 2x5 7 GA STEEL TUBE</b>	<b>WALL &amp; FLOOR GAUGE – 11 GA STEEL</b>
<b>PLUG- 7 WAY RV STYLE</b>	<b>LIGHTS- DOT LED LEGAL SEALED BEAM</b>	<b>HYDRAULIC POWER- UP/DOWN</b>		

## STANDARD FEATURES

POWDER COAT FINISH	D-RINGS MOUNTED IN BED
TOP MOUNT ON GOOSENECK FOR SPARE TIRE	DOT LEGAL IN ALL STATES
COMPLETE SAFETY BREAK-A-WAY KIT	BOARD MOUNT ON TOP OF SIDES TO EXTEND HEIGHT
HEAVY DUTY LOADING RAMPS	DUAL FUNCTION TAIL-GATE (SPREAD/DUMP)
DUAL 4” HYDRAULIC CYLINDERS	LOCKABLE STEEL BOX THAT HOUSES DEEP CYCLE BATTERY AND HYDRAULIC PUMP
(2) STABILIZER JACKS	

\***POWDER COAT FINISH**, stronger and more durable than conventional paint

\*Dual use, dump or haul equipment

\*Heavy Duty 2” x 6” x ¼” wall tube frame design

\*Lockable steel box that houses controls

\*multi-function rear gate, spread or dump

\***Heavy duty loading ramps included**

\*Brakes on all wheels

\*Dual cylinders, powered up and down

\*Board pockets to increase sidewall height to 36”

\*extra- long cord on remote control

\*equipment loading ramps are included, 14k models have rear stabilizer jacks

\*D-rings in bed

\*83” interior bed width