

GATORMADE ELITE TANDEM AXLE 20K GOOSENECK

SPECIFICATIONS

G.V.W.R. -20,000# TRAILER WEIGHT -5,900 # (20+5), 6,750 # (25+5), 7,600 # (30+5)	NET PAYLOAD -14,100 # (20+5), 13,250 # (25+5), 12,400 # (30+5)
G.A.W.R. -(PER AXLE) 8,000#	COUPLER -GOOSENECK PIPE 2-5/16" ADJUSTABLE BALL COUPLER
SAFETY CHAINS -5/16" X 35" W/SAFETY LATCH	JACKS -(2) 10,000# LIFT, 12,000# STATIC, DUAL SPEED, BOLT-ON WITH SPRING LOADED FOOT
FRAME - 12" I- BEAM @ 16 LBS PER FT.	CROSSMEMBERS - 3" CHANNEL 16" O.C. W/ BOX FRAMED KNEE BRACES
NECK - 12" I-BEAM @ 16 LBS PER FT. WITH ENCLOSED HEAD-BOARD	SIDE RAILS - 6" CHANNEL
AXLES -(2) 8,000# SINGLE WHEEL WITH ELECTRIC BRAKES ANDE-Z LUBE HUBS	SUSPENSION -MULTI-LEAF SLIPPER SPRING WITH EQUALIZER
WHEEL - 17-1/2" 8 LUG TIRE -ST215/75R/17.5 LOAD RANGE G 16 PLY	FLOOR - 2" TREATED PINE SCREWED TO CROSS-MEMBERS
LIGHTS -D.O.T. LEGAL STOP, TAIL, TURN, AND CLEARANCE	PREPERATION FINISH -METAL IS SANDBLASTED FOR SUPERIOR ADHESION FINISH - GATOR-TUFF POWDER COAT
ELEC. PLUG - 7 WAY RV	

STANDARD FEATURES

RAMPS-40" (W) x 60" (L) WITH POWER ASSIST UP AND DOWN WITH DIAMOND PLATE BOTTOM AND RAMP LOCK DOWN HANDLE	COMPLETE BREAK-AWAY KIT WITH BATTERY AND CHARGER
STEPS ON EACH SIDE OF BED WITH BOARDING HANDLES	LOCKABLE STEEL TOOL BOX WITH LID HOLDER BETWEEN GOOSENECK UPRIGHTS
102" OVERALL BED WIDTH	RUBBER MOUNTED SEALED LIGHTING
ALL WIRING SEALED IN TUBE OR CONDUIT	SAFETY REFLECTIVE MARKER TAPE
MOUNTED SPARE TIRE	DRIVER SIDE MOUNTED TYPE"ABC" FIRE EXTINGUISHER
40" TALL ENCLOSED HEADBOARD FOR LOAD PROTECTION	ALL LED LIGHTING
STAKE POCKETS 19" O.C. WITH RUB-RAIL AND CHAIN SPOOLS	WORK LIGHT BAR ON TOP OF HEADBOARD(BRAKE, TURN, EMERGENCY, SPOTLIGHT)
SELF CLEANING DOVETAIL	

OPTIONS

STAND-UP BARS FOR RAMPS	UNDER THE DECK STEEL TOOL BOX(S)	6' X 8' DECK OVER NECK	ADDITIONAL TIRE/WHEEL
RATCHET RAIL	SLIDING RATCHETS WITH STRAPS	WELDED ON D-RINGS	REMOVABLE STAKE POCKET D-RINGS
NO DOVETAIL	5 TH WHEEL GOOSENECK COUPLER	8' HEAVY DUTY RAMPS FOR FLAT DECK TRAILERS	WINCH PLATE IN DECK