

GATORMADE ELITE 21K TRI-AXLE GOOSENECK

SPECIFICATIONS

G.V.W.R. -21,000# TRAILER WEIGHT -6,500# (25+5) 7,350# (30+5) 8,300# (35+5)	NET PAYLOAD -14,500# (25+5) 13,650# (30+5) 12,700# (35+5)
G.A.W.R. -(PER AXLE) 7,000#	COUPLER -GOOSENECK PIPE 2-5/16" ADJUSTABLE BALL COUPLER
SAFETY CHAINS -5/16" X 35" W/SAFETY LATCH	JACKS -(2) 10,000# LIFT, 12,000# STATIC, DUAL SPEED, BOLT-ON WITH SPRING LOADED FOOT
FRAME -12" I- BEAM @ 19 LBS PER FT.	CROSSMEMBERS - 3" CHANNEL 16" O.C. W/ KNEE BRACES
NECK - 14" CHANNEL/12" I-BEAM	SIDE RAILS - 6" CHANNEL WITH RUB RAIL AND STAKE POCKETS
AXLES -(3) CAMBERED 7,000# SINGLE WHEEL WITH ELECTRIC BRAKES AND E-Z LUBE HUBS	SUSPENSION -MULTI-LEAF SLIPPER SPRING WITH EQUALIZER
WHEEL - 16" x 6" 8 LUG TIRE-ST235/80R/16 LOAD RANGE E 10 PLY	FLOOR - 2" TREATED PINE SCREWED TO CROSSMEMBERS
LIGHTS -D.O.T. LEGAL STOP, TAIL, TURN, AND CLEARANCE	PREPERATION FINISH -METAL IS SANDBLASTED FOR SUPERIOR ADHESION
ELEC. PLUG - 7 WAY RV	FINISH - <i>HEAVY DUTY GATOR TUFF POWDER COAT FINISH</i>

STANDARD FEATURES

40" WIDE POWER x 60" (L) ASSIST RAMPS UP AND DOWN WITH DIAMOND PLATE BOTTOM AND HANDLE	COMPLETE BREAK-AWAY KIT WITH BATTERY AND CHARGER
STEPS ON EACH SIDE OF BED WITH BOARDING HANDLES	LOCKABLE STEEL TOOL BOX WITH LID HOLDER BETWEEN GOOSENECK UPRIGHTS
102" OVERALL BED WIDTH	RUBBER MOUNTED SEALED LIGHTING
WIRING ENCLOSED IN TUBE & CONDUIT	SAFETY REFLECTIVE MARKER TAPE
MOUNTED SPARE TIRE	DRIVER SIDE MOUNTED TYPE"ABC" FIRE EXTINGUISHER
40" TALL ENCLOSED HEADBOARD FOR LOAD PROTECTION	LIFETIME ALL LED LIGHTING
SELF CLEANING DOVETAIL	WORK LIGHT BAR ON TOP OF HEADBOARD(BRAKE, TURN, EMERGENCY, SPOTLIGHT)

OPTIONS

STAND-UP RAMP BARS	SIDE MOUNT TOOL BOX	6' X 8' DECK OVER NECK
25+5, 30+5, 35+5 LENGTHS	WINCH PLATE IN DECK	STRAP RACHETS W/SLIDE TRACK
REMOVABLE STAKE POCKET D-RINGS	WELD-ON D-RINGS	NO DOVETAIL
5 th WHEEL GOOSENECK COUPLER	14 PLY RADIAL TIRE UPGRADE	