

GATORMADE TRI-AXLE 30K GOOSENECK

SPECIFICATIONS

G.V.W.R. -30,000 # TRAILER WEIGHT-9,100 # (25+5) 10,100# (30+5) 11,100# (35+5) 12,100# (40+5)	NET PAYLOAD -20,900 # (25+5) 19,900# (30+5) 18,900# (35+5) 17,900# (40+5)
G.A.W.R. -(PER AXLE) 10,000 #	COUPLER -GOOSENECK PIPE 2-5/16" ADJUSTABLE BALL COUPLER, 30K RATED
SAFETY CHAINS -5/16" X 35" W/SAFETY LATCH	JACKS -(2) 10,000# LIFT, 12,000# STATIC, DUAL SPEED, BOLT-ON WITH SPRING LOADED FOOT
FRAME -14" I- BEAM @ 22 LBS PER FT.	CROSSMEMBERS - 3" CHANNEL 16" O.C. W/ BOX FRAMED KNEE BRACES
NECK - 14" I-BEAM @ 22 LBS PER FT. WITH ENCLOSED HEAD-BOARD	SIDE RAILS - 2x6 TUBE RAIL
AXLES -(3) DEXTER 10,000 # OIL BATH DUAL WHEEL WITH ELECTRIC BRAKES	SUSPENSION -MULTI-LEAF SLIPPER SPRING WITH EQUALIZER
WHEEL - 16" x 6" 8 LUG TIRE -ST235/85R/16 LOAD RANGE E 10 PLY	FLOOR - 2" TREATED PINE SCREWED TO CROSS-MEMBERS
LIGHTS -D.O.T. LEGAL STOP, TAIL, TURN, AND CLEARANCE	PREPERATION FINISH -METAL IS SANDBLASTED FOR SUPERIOR ADHESION FINISH - GATOR-TUFF POWDER COAT
ELEC. PLUG - 7 WAY RV	

STANDARD FEATURES

RAMPS-40" (W) x 60" (L) WITH POWER ASSIST UP AND DOWN WITH DIAMOND PLATE BOTTOM AND RAMP LOCK DOWN HANDLE	COMPLETE BREAK-AWAY KIT WITH BATTERY AND CHARGER
STEPS ON EACH SIDE OF BED WITH BOARDING HANDLES(DRIVERS SIDE STEP IS LIGHTED)	LOCKABLE STEEL TOOL BOX WITH LID HOLDER BETWEEN GOOSENECK UPRIGHTS
102" OVERALL BED WIDTH	RUBBER MOUNTED SEALED LIGHTING
ALL WIRING SEALED IN TUBE OR CONDUIT	SAFETY REFLECTIVE MARKER TAPE
MOUNTED SPARE TIRE	DRIVER SIDE MOUNTED TYPE"ABC" FIRE EXTINGUISHER
40" TALL ENCLOSED HEADBOARD FOR LOAD PROTECTION	ALL LED LIGHTING
STAKE POCKETS 19" O.C. WITH RUB-RAIL AND CHAIN SPOOLS	WORK LIGHT BAR ON TOP OF HEADBOARD(BRAKE, TURN, EMERGENCY, SPOTLIGHT)
SELF CLEANING DOVETAIL	LOW PROFILE PIERCED FRAME DESIGN 35" DECK HEIGHT +/-
6"HORIZONTAL TORQUE TUBE	

OPTIONS

8' HEAVY DUTY SLIDE IN RAMPS FOR FLAT DECK TRAILERS	UNDER DECK STEEL 18" x 18" x 36" LOCKABLE STEEL STORAGE BOX	CHROME WHEEL SIMULATORS	6' X 8' DECK OVER THE NECK
5 TH WHEEL GOOSENECK COUPLER	4" SLIDE RATCHETS WITH 27' STRAP	WELD-ON D-RINGS	REMOVABLE STAKE POCKET D-RINGS
RATCHET RAIL	14 PLY RADIAL TIRE UPGRADE	WINCH PLATE IN DECK	