

GATORMADE AARDVARK ELITE 14K EQUIPMENT TRAILER

SPECIFICATIONS

G.V.W.R. -14,000# TRAILER WEIGHT - 3,620# (16+4) 4,220# (20+4)	NET PAYLOAD - 10,380# (16+4) 9,780# (20+4)
G.A.W.R. (PER AXLE)-(2)CAMBERED 7,000# WITH ELECTRIC BRAKES AND E-Z LUBE HUBS	SUSPENSION -MULTI-LEAF SPRING WITH EQUALIZER
COUPLER -STAMPED E-Z LATCH ADJUSTABLE 2-5/16" BALL COUPLER, 20,000 # RATING COUPLER HEIGHT - ADJUSTABLE, 13" -21"	TIRE - 235/80/16 RADIAL, LOAD RANGE "E", 10 PLY
SAFETY CHAINS - 5/16" x 32" W/SAFETY LATCH	WHEEL -16" x 8 LUG STANDARD
JACK -(2) BOLT-ON 10,000# LIFT, 12,000# STATIC, WITH SPRING LOADED FOOT	FLOOR -2" x 8" PRESSURE TREATED PINE SCREWED TO CROSS-MEMBERS
TONGUE - 9" CHANNEL HEAVY DUTY DESIGN, 10" BEAM NECK UPRIGHTS INTEGRAL WITH FRAME TONGUE LENGTH - 82" TONGUE WEIGHT - (+/-) 330 LBS.	LIGHTS -LED D.O.T. LEGAL STOP, TAIL, TURN, AND CLEARANCE
ELEC. PLUG - 7 WAY RV	CROSS-MEMBERS -3" CHANNEL 16" O.C.
FRAME -10" I-BEAM	FINISH -HEAVY DUTY BLACK GATOR TUFF POWDER COAT
FENDERS - BOLT-ON DOUBLE SQUARE BROKE, DIAMOND PLATE WITH BACK	PREPERATION FINISH -METAL IS SANDBLASTED FOR SUPERIOR PAINT ADHESION
DECK HEIGHT - 25"	DOVETAIL CLEARANCE FROM GROUND - 16"

STANDARD FEATURES

24" WIDE x 48" 3 BEAM LONG RAMPS THAT LAY FLAT OR STAND-UP	82" BETWEEN THE FENDERS
REFLECTIVE MARKER TAPE	COMPLETE BREAK-A-WAY SYSTEM WITH CHARGER
SPARE TIRE INCLUDED	SELF CLEANING DOVETAIL
GROMMET MOUNTED SEALED LIGHTING	STAKE POCKETS & RUBRAIL
INNOVATIVE TONGUE DESIGN INCREASES LATERAL STRENGTH AND REDUCES FRAME TWIST. WEIGHT IS TRANSFERRED FARTHER BACK ON BED REDUCING FATIGUE ON FRAME RAILS FOR A SMOOTH, SUPERIOR PULLING PERFORMANCE	(2) WORK LIGHTS ON HEADBOARD STEEL LOCKABLE TOOL BOX ON TONGUE (6) D-RINGS ON BED DUAL BOARDING STEPS

OPTIONS

PINTLE RING	TIE DOWNS & "D" RINGS
8,000 LB. AXLE UPGRADE, INCLUDES 17.5" COMMERCIAL STEEL WHEELS WITH 16 PLY TIRES	WINCH PLATE IN DECK