

GATORMADE TANDEM AXLE 14K PINTLE TRAILER

SPECIFICATIONS

G.V.W.R. -14,000# TRAILER WEIGHT -3,800# (16+5) 4,500# (20+5)	NET PAYLOAD -10,000 # (16+5) 9,500 # (20+5)
G.A.W.R. -(PER AXLE) 7,000#	COUPLER - ADJUSTABLE 2-1/2" ID PINTLE RING OR 2-5/16" BALL COUPLER
SAFETY CHAINS -5/16" X 35" W/SAFETY LATCH	JACKS -(2) 10,000# LIFT, 12,000# STATIC, BOLT-ON WITH SPRING LOADED FOOT
FRAME -10" I BEAM @ 15 LBS. PER FOOT	CROSSMEMBERS - 3" CHANNEL 19" O.C.
TONGUE - "A" STYLE 10" I BEAM	SIDE RAILS - 3x5x1/4 WALL WITH STAKE POCKETS 32" O.C.
AXLES -(2) CAMBERED 7,000# OIL WITH ELECTRIC BRAKES	SUSPENSION -MULTI-LEAF SLIPPER SPRING WITH EQUALIZER
WHEEL - 16" x 6" 8 LUG TIRE - ST235/80R/16 LOAD RANGE E 10 PLY	FLOOR - 2" TREATED PINE SCREWED TO CROSS-MEMBERS
LIGHTS - D.O.T. LEGAL STOP, TAIL, TURN, AND CLEARANCE	PREPERATION FINISH -METAL IS SANDBLASTED FOR SUPERIOR ADHESION FINISH -HEAVY DUTY GATOR TUFF POWDER COAT FINISH
ELEC. PLUG - 7 WAY RV	DECK HEIGHT - 34" +/-
COUPLER HEIGHT - 20" – 26" +/-	

STANDARD FEATURES

24" WIDE RAMPS WITH SPRING ASSIST, DIAMOND PLATED BOTTOMS AND HANDLES	COMPLETE BREAK-AWAY KIT WITH BATTERY AND CHARGER
LED TAIL LIGHTS	ADJUSTABLE COUPLER
96" OVERALL BED WIDTH	RUBBER MOUNTED SEALED LIGHTING
MODULAR SEALED WIRING HARNESS	SAFETY REFLECTIVE MARKER TAPE
SELF-CLEANING STEEL DOVE-TAIL	

OPTIONS

ALL LED LIGHTING	SIDE MOUNT TOOL BOX	WELD-ON D-RINGS REMOVABLE STAKE POCKET D-RINGS	STRAP RACHETS W/SLIDE TRACK
STAND-UP RAMP BARS	FREIGHTER DECK (NO DOVETAIL)	ADDITIONAL STAKE POCKETS	SPARE TIRE/WHEEL
RUBRAIL			