

GATORMADE 6'10" x 12' 7K GVW TANDEM AXLE UTILITY TRAILER

SPECIFICATIONS

G.V.W.R.-7,000# TRAILER WEIGHT-1,300#	NET PAYLOAD-5,700#
G.A.W.R.-3,500# PER AXLE	AXLE- (2) CAMBERED 3,500# EZ-LUBE W/BRAKES
COUPLER- 2-5/16" BALL COUPLER	SUSPENSION- MULTI-LEAF SPRING W/EQUALIZER
SAFETY CHAINS- 24" LENGTH W/SAFETY LATCH	TIRE- ST205/75/D15 6PLY LOAD RANGE C
JACK-(1) 2,000# TOP WIND, TONGUE MOUNT BOLT-ON, WITH JACK FOOT	WHEEL-15" SILVER MODULAR 5 LUG
TONGUE- 5" CHANNEL "V" STYLE INTEGRAL WITH FRAME	FLOOR-2" TREATED PINE SCREWED TO CROSSMEMBERS
TOP RAIL-2" x 2" x 1/8" ANGLE	LIGHTS-D.O.T. LEGAL STOP, TAIL, TURN, AND CLEARANCE W/ LICENSE PLATE HOLDER
FRAME-3" x 2" x 3/16" ANGLE	ELEC. PLUG- 7-WAY RV
UPRIGHTS- 2" x 2" x 1/8" ANGLE, 12" TALL UTILITY RAILS	CROSSMEMBERS- 3" x 2" x 3/16" ANGLE
PREPERATION FINISH-METAL IS SANDBLASTED FOR SUPERIOR PAINT ADHESION	FENDERS- ROLLED FORMED TEAR DROP W/BACK
FINISH-HEAVY DUTY GATOR TUFF POWDER COAT	DECK HEIGHT- (+/-) 19"
COUPLER HEIGHT- (+/-) 15"	

STANDARD FEATURES

3" x 2" ANGLE x 50" (T) RAMP GATE, W/ EXPANDED METAL AND POWER ASSIST	6'10" BETWEEN THE FENDERS
COMPLETE BREAK-A-WAY SYSTEM WITH CHARGER	2 TIE-DOWNS

OPTIONS

SPARE TIRE AND WHEEL	ALL LED LIGHTS
POLY TOOL BOX	ADDITIONAL TIE DOWNS
3" x 2" ANGLE x 60" (W) x 50" (T) SIDE RAMP GATE, 2 UPRIGHTS W/EXPANDED METAL	UPGRADE TO CHROME WHEELS UPRADE TO MAG WHEELS
ADJUSTABLE COUPLER ON TONGUE	10K GVW UPGRADE (2) 5.2K AXLES W/BRAKES